

LPG  
Forklifts  
Cushion Tire



# LPG Forklifts-Cushion Tire



CPYD15/18/20/25/30/32C



CPYD40/50C

Item	LPG Forklift-Cushion Tire (3000-6500 lbs. Capacity)								LPG Forklift-Cushion Tire (8000-10000 lbs. Capacity)	
	H3C Series								H3C Series	
Series										
Model	CPYD15C	CPYD18C	CPYD20C	CPYD20C	CPYD25C	CPYD30C	CPYD32C	CPYD40C	CPYD50C	
Rated capacity	lbs	3000	3500	4000	4000	5000	6000	6500	8000	10000
Load center	in	24	24	24	24	24	24	24	24	24
Dimensions										
Overall height (overhead guard)	in	82.7	82.7	82.7	83.0	83.0	83.0	83.0	85.8	85.8
Overall length (with fork/without fork)	in				128.7/92.5	136.8/94.5	140/97.8	141/99	153/105	157/109
Overall width (single tire)	in	37.6	37.6	37.6	42.0	42.0	44.0	44.0	50	55.9
Min. turning radius (exterior) (A single tire is the same double tires)	in	68.5	70.9	71.7	76	78.7	80.7	81.9	91	95
Weight										
Total weight	lbs	6283.2	6724.1	7231.2	8466	9480	10725	11067	13690	15498
Wheels, Chassis										
Tire size (front/rear)	in	18x6x12.125/14x5x10			21x7-15/16x6-10.5		21x8-15/16x6-10.5		22x9-16/ 18x7-12.125	22x12-16/ 18x7-12.125
Performance										
Max. traveling speed (loaded/unloaded)	mph	9.9/9.9			10.8/10.8			11.8/11.8		
Engine mode	KUBOTA WG2503				KUBOTA WG2503				KUBOTA WG3800	
Engine rated power	HP/rpm	LPG:58.3/2600	LPG:58.3/2600	LPG:58.3/2600	GAS:57.4/2600 LPG:58.3/2600				LPG:84.8/2400	
Engine rated torque	(ft*lb)/rpm	LPG:128.1/1400	LPG:128.1/1400	LPG:128.1/1400	GAS:120.4/1800 LPG:128.1/1400				LPG:208.3/1200	
Engine cylinder number		4			4			4		
Piston displacement	L	2.491			2.491			3.77		

Option: Dual fuel