



Walk- Behind Pallet Truck



Walk-Behind Pallet Truck



CBD15/20J-Li2



CBD20-150



CBD35-510/520



CBD35-530

Model		CBD15J-Li2	CBD20J-Li2	CBD20-150	CBD35-510	CBD35-520	CBD35-530
Loading capacity	lbs	3300	4400	4500	7000	7000	7000
Load center	in	24	24	24	48	24	24
Operating type		Walkie	Walkie	Walkie	Rider	Rider	Walkie
Wheels type		PU	PU	PU	PU	PU	PU
Max. lifting height	in	7.87	7.87	7.70	9.00	9.00	9.00
Overall fork width	in	21.7/27.0	21.7/27.0	21.3/23.6/25.6/27.0	27.0/7.09	27.0/8.66	27.0/8.66
Fork length	in	45	45	45/48	96	48/54/60	48/54/60
Overall length	in	60.7	60.7	68.9	141.9	93.5	87.5
Overall width	in	21.7/27	21.7/27	28.3	36.6	36.6	32.8
Overall height (With handle)	in	44	44	54.50	60.47	60.47	60.47
Min. turning radius	in	53.3	53.3	62.00	106.61	86.22	80.75
Min. aisle width for pallets 1000×1200	in	69.3	69.3	76.40	143.70	99.84	93.11
Travel speed	mph	2.6/2.8	2.6/2.8	2.2/2.5	6.8/8.7	6.8/8.7	2.5/2.8
Lift speed	in/s	-	-	3.9/4.9	6.9/7.9	6.9/7.9	6.9/7.9
Driving motor	hp	DC 1.0	DC 1.0	AC 1.5	AC 4.2	AC 4.2	AC 1.5
Battery voltage/capacity	V/Ah	24/28	48/20	24/170 (Maintenance free)	24/360	24/360	24/360
Controller		CURTIS	CURTIS	ZAPI	ZAPI	ZAPI	ZAPI
Battery weight	lbs	15	16.5	420	704	664.4	302
Service weight with battery	lbs	340	320	1330	2521	2284	2002

NOTE: 170, 150, Li2 Fork lowered height 3 in.



Walk- Behind Stacker



Walk-Behind Stacker



CBS10J-K



CDD12J-K



CTD16-960H

Model	CBS10J-K		CDD12J-K		CTD16-960H
Type	Semi-electric (Straddle)		Straddle		Straddle
Mast type	Single mast	2-Stage STD	Single mast	2-Stage STD	Full free 3-stage
Loading capacity	2000 (Rated traction weight)		2400 (Rated traction weight)		3500
Load center	24		24		24
Operating type	Handle		Pedestrian propelled		Walkie
Wheels type	Nylon/polyurethane		Polyurethane		PU
Lift height	63	79/98/118/138	63	79/98/118/138	177.2/185.0/196.9/212.6
Max. extend height	84	103/123/142/162	83	100/120/140/160	196.7/204.7/216.5/236.2
Mast lowered height	84	65/75/84/94	83	62/72/82/92	81.2/83.9/87.8/93.0
Overall length	73		70		75.2
Overall width	43-59		45-61		31.5
Min. turning radius	59		53		59
Min. aisle width for pallets 1000×1200	92.7-96.5		87		79.9
Travel speed	-		2.48/2.61		3.1/3.4
Lift speed	3.07/5.71	3.00/5.63	3.6/5.4		25.6/35.4
Battery voltage/capacity	12/120		2×12/100		24/270
Controller	-		CURTIS		ZAPI
Battery weight	72		2×54		539
Service weight with battery	870	970/988/1000/1050	1190	1272/1296/1320/1344	3320

Walk-Behind Stacker



CQDH15R

Model	CQDH15R				
		Single Scissor With Platform (Multi-valve)	Single Scissor With Platform (Magnetia-valve)		Double Scissors With Platform (Magnetic-Valve)
Type					
Mast type		-	-	-	-
Loading capacity	lbs	3000	3000	3000	2000
Load center	in	20	20	20	20
Operating type		Stand-up rider (optional electric steering)	Stand-up rider (optional electric steering)	Walking style rider (optional electric power steering)	Stand-up rider (optional electric steering)
Wheels type		PU	PU	PU	PU
Lift height	in	98/118/138/157/177/197/217	98/118/138/157/177/197/217	79/98/118/138/157/177/197/217/236	118/138/157/177/197/217
Max. extend height	in	133/153/172/192/212/232/251	133/153/172/192/212/232/251	113/133/153/172/192/212/232/251/271	159/179/198/218/238/258
Mast lowered height	in	74/83/93/103/86/92/98	74/83/93/103/86/92/98	64/74/83/93/103/86/92/99/105	84/94/103/86/92/99
Overall length	in	93/93/93/93/94/94/94	93/93/93/93/94/94/94	94/96/96/96/96/96	104/104/104/105/105/105/105
Overall width	in	47-51/37	47 ¹ 51 ⁴ /37	47 ¹ 51 ⁵ /37	49/37
Min. turning radius	in	66.6 ² /67.3 ⁴	66.6 ² /67.3 ⁴	62.5 ¹ /63.3 ⁵	68.6 ² /69.4 ⁴
Min. aisle width for pallets 1000×1200	in	111.6 ² /112.9 ⁴	111.6 ² /112.9 ⁴	107.6 ¹ /109.1 ⁵	116.5 ³ /117.4 ⁴
Travel speed, laden/unladen	mph	2.98/3.11	2.98/3.11	2.98/3.11	2.98/3.11
Lift speed, laden/unladen	in/s	3.74/4.72	3.74/4.72	3.74/4.72	3.74/4.72
Battery voltage/capacity	V/Ah	24/320(460)	24/320(460)	24/320(460)	24/320
Controller		-	-	-	-
Battery weight	lbs	570(720)	570(720)	570(720)	570
Service weight with battery	lbs	4500/4600/4700/4700/5000/5100/5200	4500/4600/4700/4700/5000/5100/5200	4500/4500/4600/4700/4700	4660/4760/4760/2060/5160/5260
Reach distance		19.7	19.7	19.7	47.2